



AS230PANT ARC STOPPER 8.0CAL DRAWSTRING PANT



FEATURES

- ▶ Arc rated / Inherent / FR / ATPV 8Cal/CM2 HRC2 (PPE2, Category 2)
- ▶ Inherently FR fabric offers excellent protection against flash fire and electric arc
- ▶ Excellent colour fastness and strength, industrial laundering follow care instructions
- ▶ Soft, lightweight and breathable, with superior moisture management
- ▶ Water-resistant, anti-soil, anti-oil finish
- ▶ 4 Pocket Design – Two front slant welt pockets & Two cargo pockets with zip closure & snap button fasten flap
- ▶ Inner knee panels (double layer) for maximum abrasion resistance
- ▶ Elastic waistband with inner drawstring
- ▶ Zip bottom for mobility
- ▶ 50mm FR segmented reflective tape below knee
- ▶ Stitched with FR thread

STANDARDS NFPA 70E HRC2, ASTM F1959/F1959M. Design certified to AS/NZS 4602.1:2011. Fabric certified to: EN ISO 11612:2015 A1, A2, B1, C1, EN ISO 11611:2008 CLASS1.

FABRIC Arc Stopper® Inherent FR Fabric and FR Components

COLOUR Navy

SIZES 5-13, 15

CLEANING AND CARE TO ISO 3758

Clean garment thoroughly. Wash temperature at 60°C max. No chlorine bleach or hydrogen peroxide either separately or in detergents. No softeners or starch. Dry cleaning with normal process. Tumble dry temperature at 60°C max. Iron temperature at 110°C max. Failure to launder properly could adversely affect the performance and arc resistance of the fabric.

SIZE CHART

Size	5	6	7	8	9	10	11	12	13	15
Waist relaxed (cm)	63.5	65.5	67.5	69.5	71.5	73.5	76	78.5	81	86
Waist stretched (cm)	120	124	128	132	136	140	145	150	155	165
Inleg (cm)	74	75	75	76	76	76	78	78	80	80