



AS230WWJKT ARC STOPPER 23CAL TTMC-W23 X-BACK WET WEATHER JACKET



THE MOST WATERPROOF JACKET WE HAVE WORKED WITH

- ▶ **Arc rated / Inherent / FR / ATPV 23Cal/CM2 HRC2 (PPE2, Category 2)**
- ▶ Inherently FR fabric with prominent arc flash protection
- ▶ The fabric's inherent arc protection is primarily provided by Lenzing™ FR, delivering permanent flame resistance with exceptional comfort and breathability
- ▶ 20,000mm+ Water Rating Rainproof and waterproof under high pressure
- ▶ Seam sealed—making it 100% watertight
- ▶ 6 pocket design – Two utility hand pockets/ Two front stow pockets below horizontal tape/ One zip stow away pocket at left front/ One FR velcro fasten inside patch pocket
- ▶ Two way resin zip, stormflap & FR velcro closure
- ▶ Hood with lining & drawstring cords
- ▶ High front chin cover
- ▶ Built-in drawstring cord at the waist
- ▶ Encapsulated elastic cuff – Inner elastic cuff for waterproofing/wind protection and outer cuff with FR velcro for fit adjustment
- ▶ 50mm FR segmented reflective heat transfer tape on body & sleeve, TTMC-W23 compliant, designed to reduce restriction and increase comfort
- ▶ Stitched with FR thread
- ▶ Excellent colour fastness and strength

STANDARDS NFPA 70E HRC2, ASTM F1959 ATPV 23CAL/CM2, Design certified to AS/NZS 1906.4:2023. Fabric certified to: EN 1149-5:2018 (EN 1149-3:2004), EN 343:2019 water penetration resistance - Class 4, water vapour resistance - Class 3. Garment certified to TTMC-W23.

FABRIC Life Safe® Fabric and FR components, 355gsm

COLOUR Orange

SIZES S-4XL, 6XL & 8XL

CLEANING AND CARE TO ISO 3758

Clean garment thoroughly. Wash temperature at 40°C max. Do not bleach. No softeners or starch. Line dry and tumble dry are recommended. Do not dry clean. Failure to launder properly could adversely affect the performance and arc resistance of the fabric. The outer fabric has been waterproofed, repeated soiling and abrasion will affect the waterproof coating.

SIZE CHART

Size	S	M	L	XL	2XL	3XL	4XL	6XL	8XL
½ Chest (cm)	59	61.5	64	66.5	69	71.5	74	79	84