

# PowerMaster Extension FED 9.8

## Technical Data Sheet

### PROPERTIES

☑ Standards	AS/NZS 1892.3
⚠ Load Rating	120kg
⚡ Electrical Properties	Complies to AS/NZS 1892.3 Section 2.4
🔥 Heat Resistance	130 Degrees Celsius
🧪 Chemical Resistance	Tested to AS/NZS 1892.3
☁ Accelerated Weathering Test	Tested to AS 2331.3.1
🛠 Warranty	3 years from date of manufacturing

### MEASUREMENTS

⚖ Weight	35.5kg
📏 Distance Between Rungs	0.305m
📏 Closed Height	5.80m
📏 Extended Height	9.80m
📏 Width	Fly: 0.370m / Base: 0.450m

### COMPONENTS

<b>A</b> Stiles	Fibreglass: ISO-PE resin with e-glass fibres
<b>B</b> Rungs	D-Rung: Aluminium 6060
<b>C</b> Feet	Swivel: 35% GF Nylon
<b>D</b> Rung Wear Strip	HD Polyethylene
<b>E</b> End Caps	35% GF Nylon
<b>F</b> Rope	Polypropylene 10mm
<b>G</b> Latch	Branach Latch: 316 Stainless steel, coated with PPA
<b>H</b> Ladder Guide Bracket	50mm Alum 6060, e-coat and black powder coat
<b>I</b> Running Guide Bracket	XF 400 Steel zinc plated with gold passivate
<b>J</b> Tie Down Bar	Steel zinc plated with gold passivate
Rivets	Zinc Plated Low Carbon Steel

