

PowerMaster Single FND 5.5

Technical Data Sheet

PROPERTIES

| | |
|-------------------------------|---------------------------------------|
| ✓ Standards | AS/NZS 1892.3 |
| ⚠ Load Rating | 160kg |
| ⚡ Electrical Properties | Complies to AS/NZS 1892.3 Section 2.4 |
| 🔥 Heat Resistance | 130 Degrees Celsius |
| 🧪 Chemical Resistance | Tested to AS/NZS 1892.3 |
| ☀ Accelerated Weathering Test | Tested to AS 2331.3.1 |
| 🛠 Warranty | 3 years from date of manufacturing |

MEASUREMENTS

| | |
|--------------------------|--------------|
| 📊 Weight | Base: 15.2kg |
| 📏 Distance Between Rungs | 0.305m |
| 📏 Height | Base: 5.485m |
| 📏 Height to Top Rung | 5.090m |
| 📏 Width | Base: 0.450m |

COMPONENTS

| | |
|-------------------|--|
| A Stiles | Fibreglass: ISO-PE resin with e-glass fibres |
| B Rungs | D-Rung: Aluminium 6060 |
| C Feet | Swivel: 35% GF Nylon |
| D Rung Wear Strip | HD Polyethylene |
| E End Caps | 35% GF Nylon |
| Rivets | Zinc Plated Low Carbon Steel |

