

GFPR707



Graphex® Carnivore®

Contact Food Glove



**Sold
as pair**

Features

- 18-gauge Graphex® cut resistant yarn offering high dexterity with maximum cut resistance
- Most dexterous Cut Level F Food handling glove available
- Contact Food Safe under AS 2070:1999 (FDA 21CFR177.2600)
- Silicone and fibreglass free construction
- 360 degree breathability
- Precurved knitted design to minimise hand fatigue

Standards & Certification

EN 388



3X4XF



US FDA 21 CFR 177.2600
Contact Food Handling



Australian Standard
AS/NZS 2161.2:2020
AS/NZS 2161.3:2020
AS/NZS 2161.4:1999
Lic. BMP 760806

Graphex® recognise that without product certification by a Notified Body all product performance testing, and adherence to standards claims cannot be independently verified. If they are not as claimed, serious safety implications for the wearer, and legal implications for the supplier and even the employer may arise.

Graphex source their entire range of Synthetic hand protection from a single manufacturing partner to ensure consistency and reliability of product, but most importantly Graphex have taken the further step of engaging a globally recognised Notified Body to audit and certify both the manufacturing process and the products.

All of Graphex's hand protection is certified as per AS/NZS and CE hand protection standards.

Specifications

Part No. GFPR707
Liner 18-gauge Graphex®

Packaging

12 **144**

Sizing & Fit

Available Sizes

- GFPR707.XS X Small
- GFPR707.S Small
- GFPR707.M Medium
- GFPR707.L Large
- GFPR707.XL X Large
- GFPR707.2XL 2X Large
- GFPR707.3XL 3X Large
- GFPR707.4XL 4X Large
- GFPR707.5XL 5X Large
- GFPR707.6XL 6X Large

Dexterity Level

Maximum Dexterity Level 5

Certified under AS/NZS 2161.2:2020

Test Report

Key Technologies



Graphex® Yarn

Graphex® yarn provides the highest levels of mechanical performance, with exceptional comfort and dexterity.

Glove Care

1. Wash + Dry according to ISO 6330:2021
2. Machine Wash 60°C
3. ECE (A) Non Phosphate Detergent.
4. 2 Kilo load, mild procedure
5. Tumble Dry 60°C

Mechanical performance Cut level is independently tested by CTC Test House.
Cut Level F is maintained after 5, 10 and 25 wash / dry cycles.

Test Report

5 Wash Report

10 Wash Report

25 Wash Report

Reach Compliance

Required Safe pH Level

Certified under AS/NZS 2161.2:2020

AZO Dye and Irritant Chemical Free

Certified under AS/NZS 2161.2:2020