

## PELCO INDUSTRIAL FIBREGLASS EXTENSION LADDER 3.0M – 5.1M

PRODUCT CODE: GRE30B



Reference Image Only

| PROPERTIES             |                                                                                                                                               |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Standards              | AS/NZS 1892:2018, AS/NZS1892.3:1996. Test Report Available.                                                                                   |
| Load rating            | Load Rated to 160kg (User, tools and equipment). Max load rating 160kg.                                                                       |
| Electrical properties  | Complies to AS/NZS 1892.3 Section 2.4                                                                                                         |
| Warranty               | 3 years*                                                                                                                                      |
| MEASUREMENTS           |                                                                                                                                               |
| Distance between rungs | 300mm                                                                                                                                         |
| Closed height          | 3.0m                                                                                                                                          |
| Extended height        | 5.1m                                                                                                                                          |
| Max working height     | 4.1m                                                                                                                                          |
| Width                  | Base 443mm, fly 360mm                                                                                                                         |
| Weight                 | 20.4kg                                                                                                                                        |
| COMPONENTS             |                                                                                                                                               |
| Stiles                 | Vinylester colour white, best resin and UV Blocker                                                                                            |
| Rungs                  | 6061 T6 aluminium 1.4mm wall thickness                                                                                                        |
| Feet                   | Heavy duty rubber feet with grip pattern                                                                                                      |
| Rope                   | Polyester                                                                                                                                     |
| Latch                  | Engineering grade nylon                                                                                                                       |
| Pole strap             | Nylon webbing encased in heavy duty plastic sleeve – 3 layers                                                                                 |
| Pole becket bridge     | Engineering grade nylon                                                                                                                       |
| Pulley                 | 316 grade stainless steel                                                                                                                     |
| Tie off rope           | 10mm nylon 8 strand multi plait with 316 grade SS Eye bolt                                                                                    |
| Pulley location        | Centre, offset or side                                                                                                                        |
| UNIQUE FEATURES        |                                                                                                                                               |
| Strength               | 70mm stile with reinforcing blocks at load bearing points: <ul style="list-style-type: none"> <li>• Head</li> <li>• Latch location</li> </ul> |
| Section overlap        | 900mm reduces flex when fully extended                                                                                                        |
| Rung securing          | Aluminium triangular shaped rungs securely glued front and back to prevent rung rotation                                                      |
| Pole strap             | 3 layers of nylon webbing and heavy-duty PVC cover                                                                                            |
| Tethering              | Optional extra tether kit is available                                                                                                        |
| Inspection and repairs | Full inspection and part repair service available from Safeworx                                                                               |

\* Warranty Terms & Conditions available from Safeworx.