

PELCO INDUSTRIAL FIBREGLASS EXTENSION LADDER 3.6M –6.3M

PRODUCT CODE: GRE36B



Reference Image Only

PROPERTIES	
Standards	AS/NZS 1892:2018, AS/NZS1892.3:1996. Test Report Available.
Load rating	Load Rated to 160kg (User, tools and equipment). Max load rating 160kg.
Electrical properties	Complies to AS/NZS 1892.3 Section 2.4
Warranty	3 years*
MEASUREMENTS	
Distance between rungs	300mm
Closed height	3.6m
Extended height	6.3m
Max working height	5.3m
Width	Base 443mm, fly 360mm
Weight	23.8kg
COMPONENTS	
Stiles	Vinylester colour white, best resin and UV Blocker
Rungs	6061 T6 aluminium 1.4mm wall thickness
Feet	Heavy duty rubber feet with grip pattern
Rope	Polyester
Latch	Engineering grade nylon
Pole strap	Nylon webbing encased in heavy duty plastic sleeve – 3 layers
Pole becket bridge	Engineering grade nylon
Pulley	316 grade stainless steel
Tie off rope	10mm nylon 8 strand multi plait with 316 grade SS Eye bolt
Pulley location	Centre, offset or side
UNIQUE FEATURES	
Strength	70mm stile with reinforcing blocks at load bearing points: <ul style="list-style-type: none"> • Head • Latch location
Section overlap	900mm reduces flex when fully extended
Rung securing	Aluminium triangular shaped rungs securely glued front and back to prevent rung rotation
Pole strap	3 layers of nylon webbing and heavy-duty PVC cover
Tethering	Optional extra tether kit is available
Inspection and repairs	Full inspection and part repair service available from Safeworx

*Warranty Terms & Conditions available from Safeworx.