ESSENTIAL HARNESS

PART CODE: H101



PRODUCT FEATURES >

- · Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for

- · Large Dorsal D Ring for easier connection.
- positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting
- designed for additional user comfort and female users, due to lower positioning of strap.
- Service Pouch on back.

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse.

STANDARDS >
















continual re-adjustment. · High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation.

















Association

ESSENTIAL HARNESS

PART CODE: H101



PRODUCT DETAILS >

- · AUS/NZ designed and engineered
- · Size ranges available Small, Standard (M-L) and Maxi (XL-2XL)
- · 10-year life span from date of manufacture



REAR DORSAL D RING



PASS THROUGH 2BAR / 3BAR BUCKLE SYSTEM



FRONT FALL ARREST ATTACHMENT POINTS



RETRO REFLECTIVE THREAD

TECHNICAL INFORMATION >

- · Webbing Material: Polyester; 45mm; UV Resilient
- Fall Arrest Hardware: Drop Forged corrosion resistant electrophoresis; high tensile steel
- Thread: Polyester; 9.81 Newtons (10kg) extension at break 19.5%
- Stitch Pattern: THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast
- · Plastic Material: UV stabilised high-density polyethylene
- · Weight: 1.2kg
- · Web Tenacity: 28kN
- Drop Forged D Rings: Alloy Steel; 40kN
- Buckle Strength: 12 to 17kN. Laser etched or hard marked on buckle









Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.



