ELITE HARNESS: MULTI-PURPOSE

PART CODE: H302



PRODUCT FEATURES >

- · Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment.
- · Liqui-Pel Technology for liquid protection, also easier to clean the harness.
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation.
- · Retro-Reflective Thread in webbing for improved visibility in low light.
- · Rear Barr D allows easier access and better weight distribution for twin retractable fall arrest devices.
- · Closed Loop Webbing system on rear Dorsal D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head.
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning.
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker.
- · Comes with Suspension Trauma Strap: One-piece Webbing with a guick connection buckle for faster deployment and connection in the event
- · Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap.
- Air COOL Padded Shoulder Straps for increased comfort and increased air flow during long periods of use.
- · Padded Legs for force disperison at moment of fall impact.
- · Confined Space Rescue Loops.
- · Quick Release Buckles. Padding under buckles.
- Large Pole strap Side D's for ease of connecting Pole Strap (work positioning).
- · Adjustable Waist Belt with tool loop attachments.
- · Service Pouch on back.
- · Comes with Harness Bag. Part Code: NBHAR

APPLICATIONS >

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse, Confined Space, Positioning Restraint.

STANDARDS >



Australian Standard







Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

12 FELLOWSHIP ROAD. GNANGARA, WA 6077 TECH SUPPORT: 1300 546 747 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PARAMOUNTSAFETY.COM 7 SIR WOOLF FISHER DRIVE, HIGHBROOK, EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 546 747 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

LINOHS.COM PARAMOUNTSAFETY.COM







ELITE HARNESS: MULTI-PURPOSE

PART CODE: H302

HEIGHT SAFETY

PRODUCT DETAILS >

- · AUS/NZ designed and engineered
- · Size ranges available Small, Standard (M-L) and Maxi (XL-2XL)
- · 10-year life span from date of manufacture



REAR Barr D ring



QUICK RELEASE



FRONT FALL ARREST ATTACHMENT POINTS



AIR COOLED PADDED SHOULDER AND LEGS STRAP



CONFINED SPACE SPREADER BAR ATTACHMENT POINTS



SIDE WORK POSITIONING D RINGS



- Webbing Material: Polyester; 45mm; UV Resilient; Liqui-pel water guard option as standard
- Fall Arrest Hardware: Drop Forged corrosion resistant electrophoresis; high strength alloy steel.
- Thread: Polyester; 9.81 Newtons (10kg) extension at break 19.5%
- Stitch Pattern: THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast
- · Plastic Material: UV stabilised high-density polyethylene
- Weight: 2.6kg
- · Web Tenacity: 28kN
- Buckle Strength: 12 to 17kN. Laser etched or hard marked on buckle
- Padding Material: Neoprene laminate



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.



12 FELLOWSHIP ROAD, GNANGARA, WA 6077 TELSTOMER SERVICE: 1300 546 747 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PARAMOUNTSAFETY.COM



