# HAND PROTECTION ARAX TOUCH GLOVES

**PRODUCT DATA SHEET: APUD-(SIZE)** 



PRODUCT CODE: APUD-(SIZE)



#### **FEATURES AND BENEFITS**

- EN388:2016 Cut Resistance Level "C"
- ASTM Cut Level 3
- Contact heat resistant to 100°C
- Good cut resistance without sacrificing comfort or dexterity
- Water based polyurethane finish coated palm
- Breathable Arax® liner
- Form fitting for comfortable all day wear
- Colour coded cuff for size identification
- Anti-static

#### **APPLICATIONS**

The Pro Choice Safety Gear range of hand protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to:

Metal Fabrication, Sheet Metal Handling, Glass/Tiles/Ceramics Handling, Rigging, Landscaping, Construction, Mining, Materials Handling, Demolition, Cut and Abrasion Risks.

## PHYSICAL DIMENSIONS

SIZE	PALM WIDTH	GLOVE LENGTH
7	8.5cm +/-	21.5cm +/-
8	9.5cm +/-	22.5cm +/-
9	10.0cm +/-	23.5cm +/-
10	10.5cm +/-	24.5cm +/-
11	10.5cm +/-	25.5cm +/-

## **AVAILABLE IN**

PRODUCT CODE	QUANTITY	CARTON
APUD-(SIZE)	12 pairs	120 pairs

#### **CUT TEST - ISO13997**

Amount of pressure required to make an incision over a 20mm travel distance using a razor sharp blade.

PERFORMANCE LEVEL	NEWTON	WEIGHT
Α	<2	200g
В	≥5	500g
С	≥10	1kg
D	≥15	1.5kg
E	≥22	2.2kg
F	≥30	3.0kg

# **PRODUCT DETAILS**

Material: Engineered Composite 13 Gauge Seamless Arax® Liner

Dip: Water based PU in Black

Cuff Type: Knitted
Colour: Blue Speckle
Sizes: 7, 8, 9, 10, 11

# **STANDARDS**

#### **CE CATEGORY:**

II Intermediary risks in accordance with:

EN420 AS/NZS 2161.2:2005 General Requirements

EN388 AS/NZS 2161.3:2016 Protection Against Mechanical Risks

Results: 4X42C

**EN407 AS/NZS 2161.4:1999** Protection Against Thermal Risks (Heat and Fire)

Results: X1XXXX
ASTM F1 790 Cut Level

Results: 3







C X1XXXX

