PILOT 2

HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

Pilot 2's co-injected, ventilated frame guarantees unequalled adaptability and comfort.











1689118 • Platinum CSP Lens • Top Vent Closed

- + \$PLATINUM (+P) COATING
- + EXCELLENT FIELD OF VISION
- + PP/TPR TWO-MATERIAL FRAME
- **+** ADJUSTABLE STRAP
- + FITS OVER PRESCRIPTION GLASSES



HIGH REQUIREMENTS AT THE SERVICE OF SAFETY

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
PILOT 2	Clear - Indirect Vented	1679110	CIO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog (⁺ 戸)
	Smoke - Indirect Vented	1679112	Cl3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog (†ア)
	CSP - Indirect Vented	1679118	Cl1	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog (†ア)
	Clear - Top Vent Closed	1689110	CIO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog (†ア)
	Smoke - Top Vent Closed	1689112	Cl3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog (ナア)
	CSP - Top Vent Closed	1689118	Cl1	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog (⁺ P)

LENS MARKING

- ₹ Platinum is a permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.
- C. The letter 'C' signifies that the product has been tested and approved for use against splashes and is appropriate for chemical
- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).
- 1. Range of luminous transmittance 43 88% (CSP).
- 3. Range of luminous transmittance 8 -18% (smoke).

TECHNOLOGIES

⊗PLATINUM'

The exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and effectively delays the appearance of fogging.

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

LENSES

- Platinum Coating a high performance anti-fog + anti-scratch coating system applied on both sides of Clear, Smoke and CSP lenses
- 99.99% UV 385 Clear
- 99.99% UV 400 Smoke & CSP

FRAME MARKING

AS/NZS 1337.1:2010: Tested and approved to AS/NZS 1337.1:2010 for medium impact and chemical splash protection. Resists a 6mm ball at 45 m/s.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS			
LENSES	PC - 2,1 mm - Curve 6		
FRAME	PP + TPR		
TEMPLES	Non Applicable		
STRAP	Nylon		
FOAM	No		
SPARE LENSES	No		

Non-contractual pictures

01/06/2020











Bollé Safety AU Pty Limited 32-40 Fairchild Street Heatherton VIC 3202 T: 1300 138 098 E: sales@bollesafety.com.au

Hong Kong Bollé Safety 818, 8/F, Ocean Centre, Harbour City, 5 Canton Road, Tsim Sha Tsui, Kowloon, Hong Kong T.: +852 2732 5038

