

PROWLER

SIMPLICITY AND PROTECTION

PROWLER features a non-slip bridge and temples for comfortable permanent wear. PROWLER's hydrated nylon frame front provides superior strength & flexibility.



1626401 • Clear



1626402 • Smoke



1626403 • Smoke / Silver Flash



1626404 • Smoke / Blue Flash



1626405 • Green Polarised








25g

- + HIGH GLOSS, HYDRATED NYLON FRAME FRONT**
- + POLYCARBONATE CO-MOULDED TEMPLE ARMS WITH THERMO PLASTIC RUBBER NOSE PAD & TEMPLE TIPS**
- + EXCEPTIONAL VISUAL CLARITY, 8 BASE CURVE**
- + FIT: MEDIUM/LARGE**

bolle
SAFETY

PROWLER

SIMPLICITY AND PROTECTION

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
PROWLER	 Clear	1626401	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke	1626402	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Smoke / Silver Flash	1626403	I3	AS/NZS 1337.1.2010	Hard coat
	 Smoke / Blue Flash	1626404	I3	AS/NZS 1337.1.2010	Hard coat
	 Green Polarised	1626405	I3	AS/NZS 1337.1.2010	Hard coat

LENS MARKING

- The letter 'I' signifies 'Medium Impact' approval.
- The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear lenses.

OCULAR LENS CATEGORY:

- Range of luminous transmittance 80-100% (clear).
- Range of luminous transmittance 8-18% (smoke, flash & polarised).

APPLICATIONS

- Driving
- Solar UV exposure
- Emergency response
- Rigging
- Assembly and production work

MAIN MARKETS

- Transport
- Mining
- Construction
- Local government and councils
- Utilities: power, gas and water
- Fisheries
- Dental

LENSES

- 2.2 mm polycarbonate
- 8 base curve
- Anti-scratch/Anti-fog coating on both sides of lenses: Clear and Smoke
- Hard coating on Silver, Blue Flash, and Polarised lenses.
- 99.9% UV 385 – Clear
- 99.9% UV 400 – Smoke, Silver Flash, Blue Flash and Polarised

FRAME MARKING

AS/NZS 1337.1:2010 Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6 mm ball at 45 m/s.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 8
FRAME	Hydrated Nylon frame front
TEMPLES	PC temple arms + EVA temple tips
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No

Non-contractual pictures

10/04/2020

Bollé Safety AU Pty Limited
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: sales@bollesafety.com.au

Hong Kong Bollé Safety
818, 8/F, Ocean Centre, Harbour City,
5 Canton Road, Tsim Sha Tsui,
Kowloon, Hong Kong
T.: +852 2732 5038

bollesafety.com.au

bolle
SAFETY